

GRP ENCLOSURES FOR BOOSTER SETS



The GRP Enclosures are **durable, cost-effective** protective cabinets designed for industrial and commercial applications. Constructed using GRP composite materials, these lightweight yet robust enclosures provide weather-resistant protection for water storage tanks, single, twin and, triple booster sets.

Featuring a one-piece construction, they require no on-site assembly, ensuring easy installation and minimal maintenance. With optional fittings such as frost protection, bulkhead lighting, and electrical sockets, these enclosures offer a **secure and versatile** solution for protecting essential equipment in various environments.

PRODUCT FEATURES



One-Piece GRP Construction – Provides high durability and eliminates the need for on-site assembly.



25mm Encapsulated Insulation – Provides thermal protection as standard.



Weather-Resistant and Low Maintenance – Ensures long-lasting protection in harsh environments.



Externally Flanged for Secure Fixing – Enables stability and easy foundation mounting.



Lightweight Design – Allows for easy transportation and installation.



Wide Range of Sizes and Configurations – Supports customized applications.



Locking Door with Cylinder Night Latch
Enhances security for enclosed equipment.



Optional Electrical and Climate Control Fittings – Includes frost protection, bulkhead lighting, and electrical sockets.

FEATURE	SPECIFICATION
TECHNOLOGY	One-piece GRP enclosures for equipment protection
MATERIAL	GRP composite construction
INSULATION	25mm encapsulated PU foam insulation as standard
ASSEMBLY	One-piece construction, no on-site assembly required
LOCKING MECHANISM	Cylinder night latch for security
EXTERNAL COLOUR OPTIONS	Available in various colours to match equipment
REGULATORY COMPLIANCE	Built to quality assurance standards
STRUCTURAL FEATURES	Externally flanged for secure foundation fixing
APPLICATION AREAS	Water storage tanks, pump stations, electrical equipment, RPZ valve protection
OPTIONAL FEATURES	Frost protection, louvred vents, bulkhead lighting, electrical sockets

MODEL	INTERNAL DIMENSIONS (MM)	EXTERNAL DIMENSIONS (MM)
1000	1000 x 1000 x 1000	1150 x 1150 x 1080
501	1000 x 500 x 1000	1150 x 650 x 1080
601	1000 x 500 x 1200	1150 x 650 x 1280
1500	1500 x 1000 x 1000	1650 x 1150 x 1080
1501	1000 x 1000 x 1500	1175 x 1175 x 1530
1818	1220 x 1220 x 1220	1370 x 1370 x 1300
2000	2000 x 1000 x 1000	2150 x 1150 x 1080
2001	1000 x 1000 x 2000	1150 x 1150 x 2080
2250	1500 x 1000 x 1500	1650 x 1150 x 1580
2501	2000 x 1000 x 1250	2150 x 1150 x 1330
2726	1828 x 1220 x 1220	1978 x 1370 x 1300
3001	2000 x 1000 x 1500	2150 x 1150 x 1580
3636	2440 x 1220 x 1220	2590 x 1370 x 1300
4001	2000 x 1000 x 2000	2150 x 1150 x 2080
4500	2500 x 1500 x 1200	2650 x 1650 x 1280
5625	2500 x 1500 x 1500	2650 x 1650 x 1580
6001	2000 x 2000 x 1500	2150 x 2150 x 1580
7500	2500 x 2000 x 1500	2650 x 2150 x 1580
8000	2000 x 2000 x 2000	2150 x 2150 x 2080
9000	3000 x 2000 x 1500	3150 x 2150 x 1580
12000	3000 x 2000 x 2000	3150 x 2150 x 2080