


MYWATER GRP ONE-PIECE TANK



The GRP One-Piece Cold Water Storage Tanks are **WRAS-approved** and designed for potable and non-potable water storage in commercial, industrial, and residential applications. Constructed from high-quality GRP materials, they feature **fully encapsulated** insulation and a sealed removable lid for maintenance

Tanks over 1,000 litres include an access manway for easy inspection. Suitable for fluid categories 1–5, they comply with BS EN 13280:2001 and are manufactured under ISO 9001:2000 quality standards. With various size options and custom configurations, these tanks provide a durable, **weather-resistant**, and efficient water storage solution.

PRODUCT FEATURES



Fully Encapsulated PU Foam Insulation – Provides excellent thermal protection for stored water.



Access Manway for Large Tanks – Facilitates inspection for tanks over 1,000 litres.



WRAS-Approved GRP Construction – Ensures high durability and compliance with water safety regulations.



Weather-Resistant Polyester Gel Coat Finish – Ensures durability in outdoor installations.



Sealed Removable Lid – Allows for easy access and maintenance.



Available in Standard and Custom Sizes – Options for restricted access and bespoke configurations.



Suitable for Fluid Categories 1–5 – Meets various water storage requirements, including backflow protection.



Manufactured to BS EN 13280:2001 & ISO 9001:2000 Standards – Guarantees quality and reliability.

FEATURE	SPECIFICATION
TECHNOLOGY	One-piece GRP cold water storage tanks
CAPACITY RANGE	90 to 12,000 litres
MATERIAL	WRAS-approved GRP with encapsulated insulation
INSULATION	CFC-free PU foam fully encapsulated within GRP
LID TYPE	Sealed, removable lid for maintenance
MAN-WAY ACCESS	Available on tanks over 1,000 litres (520 x 520mm)
TEMPERATURE RANGE	-15°C to +30°C
REGULATORY COMPLIANCE	WRAS Approved, BS EN 13280:2001, ISO 9001:2000
APPLICATION AREAS	Potable & non-potable water, process water, cooling applications
BACKFLOW PROTECTION	Suitable for fluid categories 1, 2, 3, & 4 (standard lid) and category 5 (with air gap)
EXTERNAL COATING	Polyester gel coat for outdoor weather resistance
STRUCTURAL SUPPORT	Rolled hollow steel section, fully encapsulated
INSTALLATION OPTIONS	One-piece or two-piece for restricted access
OPTIONAL FEATURES	Float valve housings, temperature sensors, drip trays, level gauges, steel support frames

PRODUCT CODE	NOMINAL CAPACITY (LITRES)	INTERNAL DIMENSIONS (MM)	EXTERNAL DIMENSIONS (MM)
90.INS	90	610 x 305 x 510	775 x 478 x 522
160.INS	160	760 x 460 x 460	950 x 655 x 499
225.INS	225	610 x 610 x 610	805 x 805 x 650
340.INS	340	915 x 610 x 610	1090 x 785 x 645
454.INS	454	1067 x 610 x 710	1255 x 805 x 745
570.INS	570	990 x 760 x 760	1150 x 925 x 800
909.INS	909	1168 x 890 x 890	1330 x 1050 x 930
1220.INS	1220	1000 x 1000 x 1220	1180 x 1180 x 1315
1500.INS	1500	1500 x 1000 x 1000	1705 x 1205 x 1095
1818.INS	1818	1220 x 1220 x 1220	1390 x 1390 x 1308
2250.INS	2250	1500 x 1000 x 1500	1705 x 1205 x 1595
2726.INS	2726	1828 x 1220 x 1220	2020 x 1410 x 1315
3185.INS	3185	2440 x 1220 x 1070	2610 x 1410 x 1165
4000.INS	4000	2000 x 2000 x 1000	2195 x 2195 x 1095
5625.INS	5625	2500 x 1500 x 1500	2695 x 1695 x 1595
7500.INS	7500	2500 x 2000 x 1500	2695 x 2195 x 1595
9000.INS	9000	3000 x 2000 x 1500	3195 x 2195 x 1595
12000.INS	12000	3000 x 2000 x 2000	3195 x 2195 x 2095