

## MYBOOST GRP CAT5 COLD WATER BOOSTER SET

The MYBOOST GRP Insulated CAT5 Cold Water Booster Set is specifically designed to meet the strict requirements for Category 5 (CAT5) water systems while be able to be situated outside and be protected from harsh weather conditions. Ideal for commercial applications such as hotels, hospitals, or large residential buildings where water quality and pressure need to meet specific regulatory standards, the CAT5 set ensures advanced filtration and pressure regulation for safe and reliable water distribution.



### PRODUCT CODE STRUCTURE

**MYBOOST**    **1C**    **40-10**    **0.75**

Product Type

No. of pumps

Pump model

Motor KW

### PRODUCT FEATURES



**Compliant with Category 5 (CAT5) standards**, making it ideal for systems that require higher-quality water and precise pressure regulation.



**Ensures compliance with stringent regulations** for water quality and pressure control in high-demand environments.



**Advanced filtration systems** ensure the water is clean and free from contaminants, meeting the highest standards of water quality.



**Advanced filtration and pressure regulation** improve the overall water safety and performance.



**Suitable for commercial applications** where water quality is critical.



**Ideal for use in hospitals, schools**, or other facilities requiring consistent water quality standards.



**Provides precise control** over water pressure and distribution.



**High efficiency**, reducing operational costs while maintaining optimal performance.

**Variable speed  
inverter**

**WRAS approved  
expansion  
vessel**

**AB air gap**

**Submersible  
multistage pump  
inside the GRP tank**



# MYBOOST GRP CAT5 COLD WATER BOOSTER SET FIXED AND VARIABLE SPECIFICATIONS

MODEL	KW	F.L.C AMPS	INLET CONNECTION (DN1)	OVERFLOW CONNECTION (DN2)	OUTLET CONNECTION (DN3)	WIDTH (MM)	LENGTH (MM)	HEIGHT (MM)
MYCAT5 187	0.75	4.8	3/4"	1 1/4"	1"	670	610	1090
MYCAT5 251	0.75	4.8	3/4"	1 1/4"	1"	670	610	1340
MYCAT 305	0.75	4.8	3/4"	1 1/4"	1"	670	610	1540
MYCAT5 375	0.75	4.8	3/4"	1 1/4"	1"	670	610	1840

MODEL	KW	F.L.C AMPS	INLET CONNECTION (DN1)	OVERFLOW CONNECTION (DN2)	OUTLET CONNECTION (DN3)	WIDTH (MM)	LENGTH (MM)	HEIGHT (MM)
MYCAT5 187V	0.75	4.8	3/4"	1 1/4"	1"	670	610	1250
MYCAT5 251V	0.75	4.8	3/4"	1 1/4"	1"	670	610	1500
MYCAT5 305V	0.75	4.8	3/4"	1 1/4"	1"	670	610	1700
MYCAT5 375V	0.75	4.8	3/4"	1 1/4"	1"	670	610	2000